



Military-Fasteners.com

P/N BACN10JS4A6CM

Description

Thread Size: 1/4", Nut Length: 1-9/32", Nut Height: 19/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	BACN10JS4A6CM
Minimum Qty (MOQ):	5 EA
NSN:	5310-01-172-5580
Schedule B:	7318.16.0085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N BACN10JS4A6CM Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque All Metal Design
Counterbore Diameter:	0.254 Inches Minimum Nut
Lubrication:	Dry Film Lubricant
Mounting Hole Diameter:	0.098 Inches Minimum And 0.103 Inches Maximum
Nut Style:	Plate
Nut Length:	1.292 Inches Maximum
Nut Height:	0.594 Inches Maximum
Plate Thickness:	0.025 Inches Nominal
Plate Width:	0.516 Inches Maximum
Nut Counterbore Depth:	0.375 Inches Minimum Nut
Nut Mounting Provision:	Straight Holes
Mounting Hole Arrangement Style:	2 Holes
Distance From Aperture Center To Mounting Hole Center:	0.495 Inches Minimum And 0.505 Inches Maximum
Center To Center Distance Between Mounting Holes Along Length:	0.998 Inches Minimum And 1.002 Inches Maximum
Temp Rating:	450.0 Deg Fahrenheit Maximum
Thread Series:	Unjf
Features Provided:	Floating Nut
Thread Quantity Per Inch:	28
Nominal Thread Size:	0.250 Inches
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5525 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Shell

How to Order

Order this locknut from our inventory online by visiting https://military-fasteners.com/nuts/clip_on+nuts/BACN10JS4A6CM and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.