

Description

BACN10TL3A6 Self-Locking Nutplate

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	BACN10TL3A6
Minimum Qty (MOQ):	5
NSN:	5310-01-113-9817
ECCN:	EAR99
National Motor Freight:	013540, Alum Nuts



P/N BACN10TL3A6 Specifications

Thread Class:	2b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque With Metallic Insert
Counterbore Diameter:	0.196 Inches Minimum Nut And 0.202 Inches Maximum Nut
Mounting Hole Diameter:	0.128 Nominal Mils And 0.135 Nominal Centimeters
Nut Style:	Plate
Nut Length:	0.975 Inches Minimum And 0.995 Inches Maximum
Nut Height:	0.580 Inches Minimum And 0.620 Inches Maximum
Plate Thickness:	0.050 Inches Minimum And 0.070 Inches Maximum
Plate Width:	0.386 Inches Minimum And 0.406 Inches Maximum
Nut Counterbore Depth:	0.139 Inches Minimum Nut And 0.155 Inches Maximum Nut
Nut Mounting Provision:	Straight Holes
Mounting Hole Arrangement Style:	2 Holes
Distance From Aperture Center To Mounting Hole Center:	0.344 Inches Nominal
Center To Center Distance Between Mounting Holes Along Length:	0.686 Inches Minimum And 0.690 Inches Maximum
Thread Series:	Unf
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.190 Inches
Material:	Aluminum Alloy 6061 Overall
Material Document And Classification:	Mil-a-12545,temper T6 Mil Spec Single Material Response Overall
Surface Treatment:	Anodize Overall Or Chromate Overall
Surface Treatment Document And Classification:	Mil-a-8625,ty 1 Mil Spec 1st Treatment Response Overall Or Mil-c-5541 Mil Spec 2nd Treatment Response Overall

How to Order

Order this self-locking nutplate from our inventory online by visiting https://military-fasteners.com/nuts/self_locking+nutplates/BACN10TL3A6 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.