

**Description**

Thread Size: 1/4", Nut Length: 3/4", Nut Height: 1/4

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	BACN10YF32
Minimum Qty (MOQ):	10
NSN:	5310-00-820-3008
Schedule B:	7318.16.0085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



## P/N BACN10YF32 Specifications

<b>Thread Class:</b>	3b
<b>Thread Direction:</b>	Right-hand
<b>Locking Feature:</b>	Prevailing Torque All Metal Design
<b>Counterbore Diameter:</b>	0.194 Inches Minimum Nut
<b>Lubrication:</b>	Dry Film Lubricant
<b>Mounting Hole Diameter:</b>	0.098 Inches Minimum And 0.103 Inches Maximum
<b>Nut Style:</b>	Plate
<b>Nut Length:</b>	0.739 Inches Maximum
<b>Nut Height:</b>	0.312 Inches Maximum
<b>Plate Thickness:</b>	0.125 Inches Nominal
<b>Plate Width:</b>	0.327 Inches Maximum
<b>Nut Counterbore Depth:</b>	0.125 Inches Minimum Nut
<b>Nut Mounting Provision:</b>	Straight Holes
<b>Mounting Hole Arrangement Style:</b>	2 Holes
<b>Distance From Aperture Center To Mounting Hole Center:</b>	0.248 Inches Minimum And 0.252 Inches Maximum
<b>Center To Center Distance Between Mounting Holes Along Length:</b>	0.498 Inches Minimum And 0.502 Inches Maximum
<b>Temp Rating:</b>	500.0 Deg Fahrenheit Nominal
<b>Thread Series:</b>	Unf
<b>Features Provided:</b>	Floating Nut
<b>Thread Quantity Per Inch:</b>	32
<b>Nominal Thread Size:</b>	0.190 Inches
<b>Material:</b>	Steel Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416 Fed Spec Single Treatment Response Overall
<b>Specification/standard Data:</b>	81205-bacn10lk Manufacturers Standard

## How to Order

Order this clip-on nut from our inventory online by visiting [https://military-fasteners.com/nuts/clip\\_on+nuts/BACN10YF32](https://military-fasteners.com/nuts/clip_on+nuts/BACN10YF32) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.