

Description

Fastener Length: 1/2

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	BACR15BA3AD8C
Minimum Qty (MOQ):	100
NSN:	5320-01-596-3867
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



* See page 2 for technical characteristics

P/N BACR15BA3AD8C Specifications

Fastener Length:	0.500 Inches Nominal
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.0913 Inches Minimum And 0.0953 Inches Maximum
Shank Style:	Straight W/radius Chamfered Tip
Head Major Diameter:	0.161 Inches Minimum And 0.184 Inches Maximum
End Item Identification:	E-3 Block 404
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Part Name Assigned By Controlling Agency:	Rivet, 100 Degree Precision Head, Close Tolerance Shank
Special Features:	Has Chemical Conversion Coating Only
Material:	Aluminum Alloy 2117 Overall
Material Document And Classification:	Qq-a-430, 2117-t4 Fed Spec Single Material Response Overall

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/BACR15BA3AD8C> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.