

Description

Fastener Length: 1/2

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	BACR15BA3AD8C
Minimum Qty (MOQ):	100
NSN:	5320-01-596-3867
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



\* See page 2 for technical characteristics

## P/N BACR15BA3AD8C Specifications

<b>Fastener Length:</b>	0.500 Inches Nominal
<b>Head Style:</b>	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
<b>Shank Diameter:</b>	0.0913 Inches Minimum And 0.0953 Inches Maximum
<b>Shank Style:</b>	Straight W/radius Chamfered Tip
<b>Head Major Diameter:</b>	0.161 Inches Minimum And 0.184 Inches Maximum
<b>End Item Identification:</b>	E-3 Block 404
<b>Countersink Angle:</b>	99.0 Degrees Minimum And 101.0 Degrees Maximum
<b>Part Name Assigned By Controlling Agency:</b>	Rivet, 100 Degree Precision Head, Close Tolerance Shank
<b>Special Features:</b>	Has Chemical Conversion Coating Only
<b>Material:</b>	Aluminum Alloy 2117 Overall
<b>Material Document And Classification:</b>	Qq-a-430, 2117-t4 Fed Spec Single Material Response Overall

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/BACR15BA3AD8C> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.