

**Description**

Fastener Length: 5/16"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	BACR15BA3B5C
Minimum Qty (MOQ):	505 EA
NSN:	5320-01-607-9800
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE  
AVAILABLE

## P/N BACR15BA3B5C Specifications

<b>Fastener Length:</b>	0.3025 Inches Minimum And 0.3225 Inches Maximum
<b>Head Style:</b>	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
<b>Shank Diameter:</b>	0.0938 Inches Minimum And 0.0963 Inches Maximum
<b>Shank Style:</b>	Straight W/radius Chamfered Tip
<b>Head Major Diameter:</b>	0.184 Inches Minimum
<b>End Item Identification:</b>	E-3 Block 404
<b>Countersink Angle:</b>	99.0 Degrees Minimum And 101.0 Degrees Maximum
<b>Material:</b>	Aluminum Alloy 5056 Overall

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/BACR15BA3B5C> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.