

Description

Fastener Length: 5/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	BACR15BA3B5C
Minimum Qty (MOQ):	505 EA
NSN:	5320-01-607-9800
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



* See page 2 for technical characteristics

P/N BACR15BA3B5C Specifications

Fastener Length:	0.3025 Inches Minimum And 0.3225 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.0938 Inches Minimum And 0.0963 Inches Maximum
Shank Style:	Straight W/radius Chamfered Tip
Head Major Diameter:	0.184 Inches Minimum
End Item Identification:	E-3 Block 404
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Aluminum Alloy 5056 Overall

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/BACR15BA3B5C> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.