

Description


Fastener Length: 5/16", roughly 1775 pieces per pound

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	BACR15BB4AD5C
Minimum Qty (MOQ):	100
NSN:	5320-01-537-2379
ECCN:	EAR99
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed



P/N BACR15BB4AD5C Specifications

Fastener Length:	0.302 Inches Minimum And 0.322 Inches Maximum
Head Style:	Small Pan
Head Height:	0.054 Inches Minimum And 0.064 Inches Maximum
Shank Diameter:	0.1250 Inches Minimum And 0.1275 Inches Maximum
Shank Style:	Straight W/radius Chamfered Tip
Head Major Diameter:	0.252 Inches Minimum And 0.262 Inches Maximum
End Item Identification:	C-135 Ccab
Part Name Assigned By Controlling Agency:	Rivet, Universal Head, Close Tolerance Shank
Material:	Aluminum Alloy 2117 Overall
Surface Treatment:	Phosphate Overall

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/BACR15BB4AD5C> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.