

**Description**

Fastener Length: 3/16"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	BACR15BB4D3
Minimum Qty (MOQ):	1000 EA
NSN:	5320-00-117-6861
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets

A circular placeholder with a thin grey border containing the text "NO IMAGE AVAILABLE" in a sans-serif font.

NO IMAGE  
AVAILABLE

## P/N BACR15BB4D3 Specifications

<b>Fastener Length:</b>	0.178 Inches Minimum And 0.198 Inches Maximum
<b>Head Style:</b>	Universal
<b>Head Height:</b>	0.054 Inches Minimum And 0.064 Inches Maximum
<b>Shank Diameter:</b>	0.124 Inches Minimum And 0.128 Inches Maximum
<b>Shank Style:</b>	Straight
<b>Head Major Diameter:</b>	0.238 Inches Minimum And 0.262 Inches Maximum
<b>Shear Strength:</b>	33000 Single Pounds Per Square Inch
<b>Material:</b>	Aluminum Alloy 2017 Overall
<b>Material Document And Classification:</b>	Qq-a-430 Fed Spec Single Material Response Overall
<b>Surface Treatment:</b>	Anodize Overall Or Oxide Film Overall
<b>Surface Treatment Document And Classification:</b>	Mil-a-8625 Mil Spec 1st Treatment Response Overall Or Mil-c-5541 Mil Spec 2nd Treatment Response Overall

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/BACR15BB4D3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.