

Description

Fastener Length: 1/2"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---------------------|
| SKU / Model: | BACR15BB8DD8 |
| Minimum Qty (MOQ): | 85 EA |
| NSN: | 5320-00-117-6534 |
| Schedule B: | 7616.10.3000 |
| ECCN: | 9A991 |
| National Motor Freight: | 013630, Alum Rivets |



* See page 2 for technical characteristics

P/N BACR15BB8DD8 Specifications

| | |
|--|---|
| Fastener Length: | 0.490 Inches Minimum And 0.510 Inches Maximum |
| Head Style: | Universal |
| Head Height: | 0.107 Inches Minimum And 0.117 Inches Maximum |
| Shank Diameter: | 0.249 Inches Minimum And 0.254 Inches Maximum |
| Shank Style: | Straight W/radius Chamfered Tip |
| Head Major Diameter: | 0.475 Inches Minimum And 0.525 Inches Maximum |
| Grip Length: | 0.115 Nominal Mils And 0.135 Nominal Centimeters |
| Shear Strength: | 37000 Single Pounds Per Square Inch |
| Material: | Aluminum Alloy 2024 Overall |
| Material Document And Classification: | Qq-a-430 Fed Spec Single Material Response Overall |
| Surface Treatment: | Anodize Overall |
| Surface Treatment Document And Classification: | Mil-c-5541 Mil Spec Single Treatment Response Overall |

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/BACR15BB8DD8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.