

**Description**

Fastener Length: 1/2"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	BACR15CD64
Minimum Qty (MOQ):	40 EA
NSN:	5320-00-789-2232
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N BACR15CD6-4 Specifications

<b>Fastener Length:</b>	0.502 Inches Nominal
<b>Head Style:</b>	Oval/truss
<b>Head Height:</b>	0.073 Inches Minimum And 0.083 Inches Maximum
<b>Shank Diameter:</b>	0.186 Inches Minimum And 0.190 Inches Maximum
<b>Shank Style:</b>	Pull Through Hollow Shank
<b>Head Major Diameter:</b>	0.537 Inches Minimum And 0.587 Inches Maximum
<b>Expansion Device:</b>	Serrated Stem-type W
<b>Grip Length:</b>	0.188 Inches Minimum And 0.250 Inches Maximum
<b>Special Features:</b>	Recommend Drill Size 10(.1935)/ Fastener Length Does Not Include Pull-through Stem -0.750
<b>Material:</b>	Aluminum Alloy 2117 Sleeve
<b>Material:</b>	Steel Stem
<b>Surface Treatment:</b>	Anodize Sleeve

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/BACR15CD6-4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.