

Description

Fastener Length: 1/2"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	BACR15CD64
Minimum Qty (MOQ):	40 EA
NSN:	5320-00-789-2232
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N BACR15CD6-4 Specifications

Fastener Length:	0.502 Inches Nominal
Head Style:	Oval/truss
Head Height:	0.073 Inches Minimum And 0.083 Inches Maximum
Shank Diameter:	0.186 Inches Minimum And 0.190 Inches Maximum
Shank Style:	Pull Through Hollow Shank
Head Major Diameter:	0.537 Inches Minimum And 0.587 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.188 Inches Minimum And 0.250 Inches Maximum
Special Features:	Recommend Drill Size 10(.1935)/ Fastener Length Does Not Include Pull-through Stem -0.750
Material:	Aluminum Alloy 2117 Sleeve
Material:	Steel Stem
Surface Treatment:	Anodize Sleeve

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/BACR15CD6-4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.