

Description

Fastener Length: 3/8

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	BACR15CE3M6
Minimum Qty (MOQ):	50
NSN:	5320-01-058-0811
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	139820, Nickel Bolts / Nails / Nuts / Rivets Etc



* See page 2 for technical characteristics

P/N BACR15CE3M6 Specifications

Fastener Length:	0.370 Inches Minimum And 0.380 Inches Maximum
Head Style:	Undersized Oval Countersunk
Head Height:	0.002 Inches Minimum And 0.005 Inches Maximum
Shank Diameter:	0.092 Inches Minimum And 0.095 Inches Maximum
Shank Style:	Straight
Head Major Diameter:	0.148 Inches Maximum
Head Minor Diameter:	0.086 Inches Minimum And 0.096 Inches Maximum
Countersink Height:	0.024 Inches Maximum
Shear Strength:	49000 Single Pounds Per Square Inch
Countersink Angle:	100.0 Degrees Nominal
Special Features:	Color Natural
Heat Treatment:	Annealed Overall
Material:	Nickel Alloy K-500 Overall
Material Document And Classification:	Qq-n-286 CI A Fed Spec Single Material Response Overall

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/BACR15CE3M6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.