

Description

Fastener Length: 3/8

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|--|
| SKU / Model: | BACR15CE3M6 |
| Minimum Qty (MOQ): | 50 |
| NSN: | 5320-01-058-0811 |
| Schedule B: | 7616.10.3000 |
| ECCN: | EAR99 |
| National Motor Freight: | 139820, Nickel Bolts / Nails / Nuts / Rivets Etc |



* See page 2 for technical characteristics

P/N BACR15CE3M6 Specifications

| | |
|--|---|
| Fastener Length: | 0.370 Inches Minimum And 0.380 Inches Maximum |
| Head Style: | Undersized Oval Countersunk |
| Head Height: | 0.002 Inches Minimum And 0.005 Inches Maximum |
| Shank Diameter: | 0.092 Inches Minimum And 0.095 Inches Maximum |
| Shank Style: | Straight |
| Head Major Diameter: | 0.148 Inches Maximum |
| Head Minor Diameter: | 0.086 Inches Minimum And 0.096 Inches Maximum |
| Countersink Height: | 0.024 Inches Maximum |
| Shear Strength: | 49000 Single Pounds Per Square Inch |
| Countersink Angle: | 100.0 Degrees Nominal |
| Special Features: | Color Natural |
| Heat Treatment: | Annealed Overall |
| Material: | Nickel Alloy K-500 Overall |
| Material Document And Classification: | Qq-n-286 CI A Fed Spec Single Material Response Overall |

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/BACR15CE3M6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.