

Description

Fastener Length: 5/16

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	BACR15CE5M5
Minimum Qty (MOQ):	100
NSN:	5320-01-019-3263
Schedule B:	7508.90.5000
ECCN:	EAR99
National Motor Freight:	139820, Nickel Bolts / Nails / Nuts / Rivets Etc

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N BACR15CE5M5 Specifications

Fastener Length:	0.307 Inches Minimum And 0.317 Inches Maximum
Head Style:	Undersized Oval Countersunk
Head Height:	0.002 Inches Minimum And 0.005 Inches Maximum
Shank Diameter:	0.155 Inches Minimum And 0.158 Inches Maximum
Shank Style:	Straight
Head Major Diameter:	0.228 Inches Minimum And 0.248 Inches Maximum
Head Minor Diameter:	0.190 Inches Minimum And 0.200 Inches Maximum
Countersink Height:	0.039 Inches Maximum
Shear Strength:	1860 Double Pounds Per Square Inch
Countersink Angle:	100.0 Degrees Nominal
Heat Treatment:	Annealed Overall
Material:	Nickel Alloy 400 Overall
Material Document And Classification:	Qq-n-281 Fed Spec Single Material Response Overall
Specification/standard Data:	81205-bacr15ce Manufacturers Standard

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/BACR15CE5M5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.