

Description

Fastener Length: 7/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|--------------------------------------------------|
| SKU / Model: | BACR15CE5M7 |
| Minimum Qty (MOQ): | 40 EA |
| NSN: | 5320-01-008-6896 |
| Schedule B: | 7508.90.5000 |
| ECCN: | EAR99 |
| National Motor Freight: | 139820, Nickel Bolts / Nails / Nuts / Rivets Etc |



* See page 2 for technical characteristics

P/N BACR15CE5M7 Specifications

| | |
|----------------------------------------------|-------------------------------------------------------------|
| Fastener Length: | 0.433 Inches Minimum And 0.443 Inches Maximum |
| Head Style: | Undersized Oval Countersunk |
| Head Height: | 0.002 Inches Minimum And 0.005 Inches Maximum |
| Shank Diameter: | 0.155 Inches Minimum And 0.158 Inches Maximum |
| Shank Style: | Straight |
| Head Major Diameter: | 0.228 Inches Minimum And 0.248 Inches Maximum |
| Head Minor Diameter: | 0.190 Inches Minimum And 0.200 Inches Maximum |
| Countersink Height: | 0.039 Inches Maximum |
| Shear Strength: | 1920 Double Pounds Per Square Inch |
| Countersink Angle: | 100.0 Degrees Nominal |
| Material: | Nickel Alloy 400 Overall |
| Material Document And Classification: | Qq-n-281,annealed Fed Spec Single Material Response Overall |
| Specification/standard Data: | 81205-bacr15ce Manufacturers Standard |

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/BACR15CE5M7> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.