

**Description**

Fastener Length: 7/16"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	BACR15CE5M7
Minimum Qty (MOQ):	40 EA
NSN:	5320-01-008-6896
Schedule B:	7508.90.5000
ECCN:	EAR99
National Motor Freight:	139820, Nickel Bolts / Nails / Nuts / Rivets Etc

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N BACR15CE5M7 Specifications

<b>Fastener Length:</b>	0.433 Inches Minimum And 0.443 Inches Maximum
<b>Head Style:</b>	Undersized Oval Countersunk
<b>Head Height:</b>	0.002 Inches Minimum And 0.005 Inches Maximum
<b>Shank Diameter:</b>	0.155 Inches Minimum And 0.158 Inches Maximum
<b>Shank Style:</b>	Straight
<b>Head Major Diameter:</b>	0.228 Inches Minimum And 0.248 Inches Maximum
<b>Head Minor Diameter:</b>	0.190 Inches Minimum And 0.200 Inches Maximum
<b>Countersink Height:</b>	0.039 Inches Maximum
<b>Shear Strength:</b>	1920 Double Pounds Per Square Inch
<b>Countersink Angle:</b>	100.0 Degrees Nominal
<b>Material:</b>	Nickel Alloy 400 Overall
<b>Material Document And Classification:</b>	Qq-n-281,annealed Fed Spec Single Material Response Overall
<b>Specification/standard Data:</b>	81205-bacr15ce Manufacturers Standard

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/BACR15CE5M7> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.