

P/N BACR15CE5M9

Description

Fastener Length: 1/2"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: BACR15CE5M9

Minimum Qty (MOQ): 20 EA

NSN: 5320-01-008-6897

Schedule B: 7508.90.5000

ECCN: EAR99

National Motor Freight: 139820, Nickel Bolts / Nails / Nuts / Rivets Etc



^{*} See page 2 for technical characteristics

P/N BACR15CE5M9 Specifications

| Fastener Length: | 0.557 Inches Minimum And 0.567 Inches Maximum |
|---------------------------------------|---|
| Head Style: | Undersized Oval Countersunk |
| Head Height: | 0.002 Inches Minimum And 0.005 Inches Maximum |
| Shank Diameter: | 0.155 Inches Minimum And 0.158 Inches Maximum |
| Shank Style: | Straight |
| Head Major Diameter: | 0.228 Inches Minimum And 0.248 Inches Maximum |
| Head Minor Diameter: | 0.190 Inches Minimum And 0.200 Inches Maximum |
| Countersink Height: | 0.039 Inches Maximum |
| Shear Strength: | 1920 Double Pounds Per Square Inch |
| Countersink Angle: | 100.0 Degrees Nominal |
| Material: | Nickel Alloy 400 Overall |
| Material Document And Classification: | Qq-n-281,annealed Fed Spec Single Material Response Overall |
| Specification/standard Data: | 81205-bacr15ce Manufacturers Standard |

How to Order

Order this solid rivet from our inventory online by visiting https://military-fasteners.com/rivets/solid+rivets/BACR15CE5M9 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/rivets/solid+rivets/BACR15CE5M9 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/rivets/solid+rivets/BACR15CE5M9 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/rivets/solid+rivets/BACR15CE5M9 and selecting the quantity you want then click "add to cart".