

Description

BACR15CE6D11 Solid Rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---------------------|
| SKU / Model: | BACR15CE6D11 |
| Minimum Qty (MOQ): | 100 |
| NSN: | 5320-01-221-1842 |
| ECCN: | EAR99 |
| National Motor Freight: | 013630, Alum Rivets |



* See page 2 for technical characteristics

P/N BACR15CE6D11 Specifications

| | |
|---|--|
| Fastener Length: | 0.6775 Inches Minimum And 0.6975 Inches Maximum |
| Head Style: | Undersized Oval Countersunk |
| Head Height: | 0.003 Inches Minimum And 0.006 Inches Maximum |
| Shank Diameter: | 0.186 Inches Minimum And 0.189 Inches Maximum |
| Shank Style: | Straight |
| Head Major Diameter: | 0.2966 Inches Minimum And 0.3016 Inches Maximum |
| Head Minor Diameter: | 0.198 Inches Minimum And 0.208 Inches Maximum |
| Countersink Height: | 0.046 Inches Nominal |
| Shear Strength: | 33000 Single Pounds Per Square Inch |
| Countersink Angle: | 99.5 Degrees Minimum And 100.5 Degrees Maximum |
| Heat Treatment: | T-4 Solution Heat Treated Overall |
| Material: | Aluminum Alloy 2017 Overall |
| Material Document And Classification: | Qq-a-430 Fed Spec Single Material Response Overall |
| Surface Treatment: | Anodize Or Chromate Overall |
| Surface Treatment Document And Classification: | Mil-a-8625 Mil Spec 1st Treatment Response Or Mil-c-5541 Mil Spec 2nd Treatment Response Overall |
| Specification/standard Data: | 80205-nas1097 Professional/Industrial Association Standard |

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/BACR15CE6D11> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.