

**Description**

Fastener Length: 1/4"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	BACR15CE6M4
Minimum Qty (MOQ):	80 EA
NSN:	5320-01-207-0347
Schedule B:	7508.90.5000
ECCN:	EAR99
National Motor Freight:	139820, Nickel Bolts / Nails / Nuts / Rivets Etc

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N BACR15CE6M4 Specifications

<b>Fastener Length:</b>	0.245 Inches Minimum And 0.255 Inches Maximum
<b>Head Style:</b>	Undersized Oval Countersunk
<b>Head Height:</b>	0.004 Inches Minimum And 0.007 Inches Maximum
<b>Shank Diameter:</b>	0.186 Inches Minimum And 0.189 Inches Maximum
<b>Shank Style:</b>	Straight W/radius Chamfered Tip
<b>Head Major Diameter:</b>	0.293 Inches Minimum And 0.298 Inches Maximum
<b>Head Minor Diameter:</b>	0.198 Nominal Mils And 0.208 Nominal Centimeters
<b>Countersink Height:</b>	0.048 Inches Nominal
<b>Countersink Angle:</b>	99.5 Degrees Minimum And 100.5 Degrees Maximum
<b>Heat Treatment:</b>	Annealed Overall
<b>Material:</b>	Nickel Alloy 400 Overall
<b>Material Document And Classification:</b>	Qq-n-281,c1 A Fed Spec Single Material Response Overall

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/BACR15CE6M4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.