

Description

Fastener Length: 3/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	BACR15CE6M7
Minimum Qty (MOQ):	75 EA
NSN:	5320-01-014-1234
Schedule B:	7508.90.5000
ECCN:	EAR99
National Motor Freight:	139820, Nickel Bolts / Nails / Nuts / Rivets Etc



* See page 2 for technical characteristics

P/N BACR15CE6M7 Specifications

Fastener Length:	0.432 Inches Minimum And 0.442 Inches Maximum
Head Style:	Undersized Oval Countersunk
Head Height:	0.016 Inches Maximum
Shank Diameter:	0.186 Inches Minimum And 0.189 Inches Maximum
Shank Style:	Straight
Head Major Diameter:	0.279 Inches Minimum And 0.298 Inches Maximum
Head Minor Diameter:	0.198 Inches Minimum And 0.208 Inches Maximum
Countersink Height:	0.048 Inches Maximum
Countersink Angle:	100.0 Degrees Nominal
Material:	Nickel Alloy 400 Overall
Material Document And Classification:	Qq-n-281,annealed Fed Spec Single Material Response Overall
Specification/standard Data:	81205-bacr15ce Manufacturers Standard

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/BACR15CE6M7> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.