

## P/N BACR15DN3AD5

### **Description**

Fastener Length: 1/4"

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model:	BACR15DN3AD5
Minimum Qty (MOQ):	255 EA
NSN:	5320-00-052-1997
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets



<sup>\*</sup> See page 2 for technical characteristics

# **P/N BACR15DN3AD5 Specifications**

Fastener Length:	0.312 Inches Nominal
Head Style:	Universal
Head Height:	0.067 Inches Minimum And 0.077 Inches Maximum
Shank Diameter:	0.098 Inches Nominal
Shank Style:	Straight
Head Major Diameter:	0.296 Inches Minimum And 0.328 Inches Maximum
Material:	Aluminum Alloy 2117 Overall
Material Document And Classification:	Qq-a-430,t4 Fed Spec Single Material Response Overall
Surface Treatment:	Oxide Film Overall
Surface Treatment Document And Classification:	Mil-c-5541 Mil Spec Single Treatment Response Overall

## **How to Order**

Order this solid rivet from our inventory online by visiting <a href="https://military-fasteners.com/rivets/solid+rivets/BACR15DN3AD5">https://military-fasteners.com/rivets/solid+rivets/BACR15DN3AD5</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.