

Description

Fastener Length: 1/2"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---------------------|
| SKU / Model: | BACR15DN5AD8 |
| Minimum Qty (MOQ): | 100 EA |
| NSN: | 5320-00-936-4626 |
| Schedule B: | 7616.10.3000 |
| ECCN: | EAR99 |
| National Motor Freight: | 013630, Alum Rivets |

NO IMAGE
AVAILABLE

P/N BACR15DN5AD8 Specifications

| | |
|---|---|
| Fastener Length: | 0.490 Inches Minimum And 0.510 Inches Maximum |
| Head Style: | Universal |
| Head Height: | 0.067 Inches Minimum And 0.077 Inches Maximum |
| Shank Diameter: | 0.156 Inches Nominal |
| Shank Style: | Straight |
| Head Major Diameter: | 0.296 Inches Minimum And 0.328 Inches Maximum |
| Material: | Aluminum Alloy 2117 Overall |
| Material Document And Classification: | Qq-a-430 Fed Spec Single Material Response Overall |
| Surface Treatment: | Chromate Overall |
| Surface Treatment Document And Classification: | Mil-c-5541 Mil Spec Single Treatment Response Overall |

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/BACR15DN5AD8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.