

Description

Fastener Length: 3/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	BACR15DP3AD6
Minimum Qty (MOQ):	500 EA
NSN:	5320-00-936-6189
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets



* See page 2 for technical characteristics

P/N BACR15DP3AD6 Specifications

Fastener Length:	0.365 Inches Minimum And 0.385 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.094 Inches Nominal
Shank Style:	Straight With Tapered Tip
Head Major Diameter:	0.175 Inches Minimum And 0.183 Inches Maximum
Chamfer Length:	0.023 Inches Nominal
Tip Diameter:	Any Acceptable
Grip Length:	Any Acceptable
Countersink Angle:	100.0 Degrees Nominal
Material:	Aluminum Alloy 2117 Overall
Surface Treatment:	Oxide Film Overall
Surface Treatment Document And Classification:	Mil-c-5541 Mil Spec Single Treatment Response Overall

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/BACR15DP3AD6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.