

P/N BACR15DP4AD8

Description

Fastener Length: 1/2"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	BACR15DP4AD8
Minimum Qty (MOQ):	145 EA
NSN:	5320-00-823-4934
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets



^{*} See page 2 for technical characteristics

P/N BACR15DP4AD8 Specifications

Fastener Length:	0.500 Inches Nominal
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.125 Inches Nominal
Shank Style:	Straight
Head Major Diameter:	0.221 Inches Minimum And 0.229 Inches Maximum
Countersink Angle:	100.0 Degrees Nominal
Special Features:	Coated With Sealing Compound E-776sr Mil-s-4383
Material:	Aluminum Alloy 2117 Overall
Material Document And Classification:	Qq-a-430,alloy 2117,t4 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall Or Oxide Film Overall
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec 1st Treatment Response Overall Or Mil-c-5541 Mil Spec 2nd Treatment Response Overall

How to Order

Order this solid rivet from our inventory online by visiting https://military-fasteners.com/rivets/solid+rivets/BACR15DP4AD8 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.