

# P/N BACR15DP5AD28

### **Description**

Fastener Length: 1/2"

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model:	BACR15DP5AD28
Minimum Qty (MOQ):	5 EA
NSN:	5320-00-936-6190
Schedule B:	7616.10.3000
ECCN:	N/A
National Motor Freight:	013630, Alum Rivets



<sup>\*</sup> See page 2 for technical characteristics

# **P/N BACR15DP5AD28 Specifications**

Fastener Length:	0.500 Inches Nominal
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.156 Inches Nominal
Shank Style:	Straight
Head Major Diameter:	0.282 Inches Minimum And 0.290 Inches Maximum
Countersink Angle:	100.0 Degrees Nominal
Material:	Aluminum Alloy 2117 Overall
Surface Treatment:	Oxide Film Overall
Surface Treatment Document And Classification:	Mil-c-5541 Mil Spec Single Treatment Response Overall

## **How to Order**

Order this solid rivet from our inventory online by visiting <a href="https://military-fasteners.com/rivets/solid+rivets/BACR15DP5AD28">https://military-fasteners.com/rivets/solid+rivets/BACR15DP5AD28</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.