

Description

Fastener Length: 1/2"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---------------------|
| SKU / Model: | BACR15DP5AD8 |
| Minimum Qty (MOQ): | 80 EA |
| NSN: | 5320-00-936-6190 |
| Schedule B: | 7616.10.3000 |
| ECCN: | EAR99 |
| National Motor Freight: | 013630, Alum Rivets |



* See page 2 for technical characteristics

P/N BACR15DP5AD8 Specifications

| | |
|--|--|
| Fastener Length: | 0.500 Inches Nominal |
| Head Style: | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer) |
| Shank Diameter: | 0.156 Inches Nominal |
| Shank Style: | Straight |
| Head Major Diameter: | 0.282 Inches Minimum And 0.290 Inches Maximum |
| Countersink Angle: | 100.0 Degrees Nominal |
| Material: | Aluminum Alloy 2117 Overall |
| Surface Treatment: | Oxide Film Overall |
| Surface Treatment Document And Classification: | Mil-c-5541 Mil Spec Single Treatment Response Overall |

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/BACR15DP5AD8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.