

Description

Fastener Length: 13/16"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	BACR15DR3AC12
Minimum Qty (MOQ):	30 EA
NSN:	5320-01-589-2336
Schedule B:	7318.23.0000
ECCN:	EAR99



NO IMAGE
AVAILABLE

P/N BACR15DR3AC12 Specifications

Fastener Length:	0.818 Inches Nominal
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.094 Inches Nominal
Shank Style:	Pull Through Hollow Shank
Head Major Diameter:	0.179 Inches Nominal
Countersink Angle:	98.5 Degrees Minimum And 101.5 Degrees Maximum
Material:	Iron Alloy 660 Sleeve
Material:	Steel Comp 303 Stem
Material Document And Classification:	Ams 5731 Assn Std Single Material Response Sleeve
Material Document And Classification:	Astm A493 Assn Std Single Material Response Stem
Surface Treatment:	Cadmium Sleeve
Surface Treatment:	Passivate Stem
Surface Treatment Document And Classification:	Qq-p-35, Type Ii Or Viii Fed Spec Single Treatment Response Stem
Surface Treatment Document And Classification:	Qq-p-416, Type Ii, Class 2 Fed Spec Single Treatment Response Sleeve

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/BACR15DR3AC12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.