

Description

Fastener Length: 3/4"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	BACR15DS7D12
Minimum Qty (MOQ):	60 EA
NSN:	5320-01-255-4640
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets



* See page 2 for technical characteristics

P/N BACR15DS7D12 Specifications

Fastener Length:	0.7500 Inches Nominal
Head Style:	Undersized Oval Countersunk
Head Height:	0.004 Inches Minimum And 0.006 Inches Maximum
Shank Diameter:	0.220 Inches Minimum And 0.222 Inches Maximum
Shank Style:	Straight W/radius Chamfered Tip
Head Major Diameter:	0.324 Inches Maximum
Head Minor Diameter:	0.237 Nominal Mils And 0.247 Nominal Centimeters
Countersink Height:	0.046 Inches Maximum
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Heat Treatment:	T-3 Solution Heat Treated Overall
Material:	Aluminum Alloy 2017 Overall
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall Or Chromate Overall
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec 1st Treatment Response Overall Or Mil-c-5541 Mil Spec 2nd Treatment Response Overall

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/BACR15DS7D12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.