

Description

Fastener Length: 19/64"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	BACR15DS7D5
Minimum Qty (MOQ):	65 EA
NSN:	5320-01-215-5421
Schedule B:	7616.10.3000
ECCN:	9A991
National Motor Freight:	013630, Alum Rivets

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N BACR15DS7D5 Specifications

Fastener Length:	0.3025 Inches Minimum And 0.3225 Inches Maximum
Head Style:	Oval Countersunk
Shank Diameter:	0.220 Inches Minimum And 0.222 Inches Maximum
Shank Style:	Straight W/radius Chamfered Tip
Head Major Diameter:	0.319 Inches Minimum And 0.324 Inches Maximum
Shear Strength:	33000 Single Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Heat Treatment:	T-4 Solution Heat Treated Overall
Material:	Aluminum Alloy 2017 Overall
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625 Ty 2 Cl 1 Mil Spec Single Treatment Response Overall

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/BACR15DS7D5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.