

P/N BACR15DS9D9

Military-Fasteners.com

#### Description

Fastener Length: 9/16"

\* Manufacturer certifications are shipped with your order  $\underline{\mathsf{FREE}}$  of charge

### Order this part online

#### **Additional Information**

SKU / Model:	BACR15DS9D9
Minimum Qty (MOQ):	30 EA
NSN:	5320-01-324-5031
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets



# P/N BACR15DS9D9 Specifications

Fastener Length:	0.5525 Inches Minimum And 0.5725 Inches Maximum
Head Style:	Undersized Oval Countersunk
Head Height:	0.004 Inches Minimum And 0.006 Inches Maximum
Shank Diameter:	0.282 Inches Minimum And 0.285 Inches Maximum
Shank Style:	Straight W/radius Chamfered Tip
Head Major Diameter:	0.424 Inches Maximum
Head Minor Diameter:	0.337 Nominal Mils And 0.347 Nominal Centimeters
Countersink Height:	0.061 Inches Maximum
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Aluminum Alloy 2017 Overall
Material Document And Classification:	Mil-f-5674 Mil Spec Single Material Response Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625,type 2,class 1 Mil Spec Single Treatment Response Overall

## How to Order

Order this solid rivet from our inventory online by visiting <u>https://military-fasteners.com/rivets/solid+rivets/BACR15DS9D9</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.