

Description

Fastener Length: 9/16"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---------------------|
| SKU / Model: | BACR15ET7D9 |
| Minimum Qty (MOQ): | 130 EA |
| NSN: | 5320-01-265-4827 |
| Schedule B: | 7616.10.3000 |
| ECCN: | EAR99 |
| National Motor Freight: | 013630, Alum Rivets |



NO IMAGE
AVAILABLE

P/N BACR15ET7D9 Specifications

| | |
|---|--|
| Fastener Length: | 0.552 Inches Minimum And 0.572 Inches Maximum |
| Head Style: | Universal |
| Head Height: | 0.080 Inches Minimum And 0.090 Inches Maximum |
| Shank Diameter: | 0.2170 Inches Minimum And 0.2195 Inches Maximum |
| Shank Style: | Straight |
| Head Major Diameter: | 0.356 Inches Minimum And 0.394 Inches Maximum |
| Shear Strength: | 33000 Single Pounds Per Square Inch |
| Heat Treatment: | T-4 Solution Heat Treated Overall |
| Material: | Aluminum Alloy 2017 Overall |
| Material Document And Classification: | Qq-a-430 Fed Spec Single Material Response Overall |
| Surface Treatment: | Anodize Overall Or Chromate Overall |
| Surface Treatment Document And Classification: | Mil-a-8625 Mil Spec 1st Treatment Response Overall Or Mil-c-5541 Mil Spec 2nd Treatment Response Overall |

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/BACR15ET7D9> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.