

Description

Fastener Length: 3/4"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	BACR15ET9D12
Minimum Qty (MOQ):	130 EA
NSN:	5320-00-804-3999
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



* See page 2 for technical characteristics

P/N BACR15ET9D12 Specifications

Fastener Length:	0.740 Inches Minimum And 0.760 Inches Maximum
Head Style:	Universal
Head Height:	0.107 Inches Minimum And 0.117 Inches Maximum
Shank Diameter:	0.280 Inches Minimum And 0.285 Inches Maximum
Shank Style:	Straight
Head Major Diameter:	0.475 Inches Minimum And 0.525 Inches Maximum
Shear Strength:	33000 Single Pounds Per Square Inch
Material:	Aluminum Alloy 2017 Overall
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625,ty 2,cl 1 Mil Spec Single Treatment Response Overall
Specification/standard Data:	81205-bacr15wd Manufacturers Standard

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/BACR15ET9D12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.