

Description

Fastener Length: 7/16"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	BACR15FT5D7C
Minimum Qty (MOQ):	505 EA
NSN:	5320-01-436-6473
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N BACR15FT5D7C Specifications

Fastener Length:	0.428 Inches Minimum And 0.448 Inches Maximum
Head Style:	Small Pan
Head Height:	0.067 Inches Minimum And 0.077 Inches Maximum
Shank Diameter:	0.1560 Inches Minimum And 0.1585 Inches Maximum
Shank Style:	Straight
Head Major Diameter:	0.234 Inches Minimum And 0.247 Inches Maximum
Material:	Aluminum Alloy 2017 Overall
Surface Treatment:	Chromate Overall
Surface Treatment Document And Classification:	Mil-c-5541, Cl 1a Mil Spec Single Treatment Response Overall

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/BACR15FT5D7C> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.