

Description

Fastener Length: 1/4

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|--------------------|------------------|
| SKU / Model: | BACR15GF3D4 |
| Minimum Qty (MOQ): | 100 |
| NSN: | 5320-01-589-7165 |
| Schedule B: | 7616.10.3000 |
| ECCN: | EAR99 |



* See page 2 for technical characteristics

P/N BACR15GF3D4 Specifications

| | |
|---|---|
| Fastener Length: | 0.2500 Inches Nominal |
| Head Style: | Undersized Oval Countersunk |
| Head Height: | 0.1190 Inches Minimum And 0.1192 Inches Maximum |
| Shank Diameter: | 0.094 Inches Nominal |
| Shank Style: | Straight W/radius Chamfered Tip |
| Head Major Diameter: | 0.132 Inches Minimum And 0.136 Inches Maximum |
| Head Minor Diameter: | 0.086 Inches Minimum And 0.096 Inches Maximum |
| Countersink Height: | 0.223 Inches Nominal |
| Shear Strength: | 257 Single Pounds Per Square Inch |
| Countersink Angle: | 100.0 Degrees Nominal |
| Material: | Aluminum Alloy 2017 Washer |
| Material Document And Classification: | Qq-a-430 Fed Spec Single Material Response Washer |
| Surface Treatment: | Chromate Washer |
| Surface Treatment Document And Classification: | Mil-c-5541, Type 1a Mil Spec Single Treatment Response Washer |

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/BACR15GF3D4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.