

Description

Fastener Length: 5/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	BACR15GF3D5
Minimum Qty (MOQ):	130 EA
NSN:	5320-01-589-7166
Schedule B:	7616.10.3000
ECCN:	EAR99



* See page 2 for technical characteristics

P/N BACR15GF3D5 Specifications

Fastener Length:	0.3125 Inches Nominal
Head Style:	Undersized Oval Countersunk
Head Height:	0.1190 Inches Minimum And 0.1192 Inches Maximum
Shank Diameter:	0.094 Inches Nominal
Shank Style:	Straight W/radius Chamfered Tip
Head Major Diameter:	0.132 Inches Minimum And 0.136 Inches Maximum
Head Minor Diameter:	0.086 Inches Minimum And 0.096 Inches Maximum
Countersink Height:	0.223 Inches Nominal
Shear Strength:	257 Single Pounds Per Square Inch
Countersink Angle:	100.0 Degrees Nominal
Material:	Aluminum Alloy 2017 Washer
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Washer
Surface Treatment:	Chromate Washer
Surface Treatment Document And Classification:	Mil-c-430, Class 1a Mil Spec Single Treatment Response Washer

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/BACR15GF3D5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.