

**Description**

Fastener Length: 7/16"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	BACR15GF3D7
Minimum Qty (MOQ):	335 EA
NSN:	5320-01-589-7171
Schedule B:	7616.10.3000
ECCN:	EAR99



NO IMAGE  
AVAILABLE

## P/N BACR15GF3D7 Specifications

<b>Fastener Length:</b>	0.4375 Inches Nominal
<b>Head Style:</b>	Undersized Oval Countersunk
<b>Head Height:</b>	0.1190 Inches Minimum And 0.1192 Inches Maximum
<b>Shank Diameter:</b>	0.094 Inches Nominal
<b>Shank Style:</b>	Straight W/radius Chamfered Tip
<b>Head Major Diameter:</b>	0.132 Inches Minimum And 0.136 Inches Maximum
<b>Head Minor Diameter:</b>	0.086 Inches Minimum And 0.096 Inches Maximum
<b>Countersink Height:</b>	0.223 Inches Nominal
<b>Shear Strength:</b>	257 Single Pounds Per Square Inch
<b>Countersink Angle:</b>	100.0 Degrees Nominal
<b>Material:</b>	Aluminum Alloy 2017 Washer
<b>Material Document And Classification:</b>	Qq-a-430 Fed Spec Single Material Response Washer
<b>Surface Treatment:</b>	Chromate Washer
<b>Surface Treatment Document And Classification:</b>	Mil-c-430, Class 1a Mil Spec Single Treatment Response Washer

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/BACR15GF3D7> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.