

**Description**

Fastener Length: 3/16"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	BACR15GF5D3
Minimum Qty (MOQ):	200 EA
NSN:	5320-01-112-2473
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N BACR15GF5D3 Specifications

<b>Fastener Length:</b>	0.185 Inches Minimum And 0.195 Inches Maximum
<b>Head Style:</b>	Undersized Oval Countersunk
<b>Head Height:</b>	0.003 Inches Minimum And 0.006 Inches Maximum
<b>Shank Diameter:</b>	0.155 Inches Minimum And 0.158 Inches Maximum
<b>Shank Style:</b>	Straight W/radius Chamfered Tip
<b>Head Major Diameter:</b>	0.248 Inches Maximum
<b>Head Minor Diameter:</b>	0.190 Nominal Mils And 0.200 Nominal Centimeters
<b>Countersink Height:</b>	0.039 Inches Maximum
<b>Countersink Angle:</b>	99.5 Degrees Minimum And 100.5 Degrees Maximum
<b>Heat Treatment:</b>	T-4 Solution Heat Treated Overall
<b>Material:</b>	Aluminum Alloy 2017 Overall
<b>Material Document And Classification:</b>	Qq-a-430 Fed Spec Single Material Response Overall
<b>Surface Treatment:</b>	Anodize Overall
<b>Surface Treatment Document And Classification:</b>	Mil-a-8625,type 2 Mil Spec Single Treatment Response Overall

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/BACR15GF5D3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.