

Description

Fastener Length: 7/16

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	BACR15GF6D7
Minimum Qty (MOQ):	50
NSN:	5320-01-589-7173
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



\* See page 2 for technical characteristics

## P/N BACR15GF6D7 Specifications

<b>Fastener Length:</b>	0.4375 Inches Nominal
<b>Head Style:</b>	Undersized Oval Countersunk
<b>Head Height:</b>	0.2438 Inches Minimum And 0.2440 Inches Maximum
<b>Shank Diameter:</b>	0.188 Inches Nominal
<b>Shank Style:</b>	Straight W/radius Chamfered Tip
<b>Head Major Diameter:</b>	0.281 Inches Minimum And 0.285 Inches Maximum
<b>Head Minor Diameter:</b>	0.198 Inches Minimum And 0.208 Inches Maximum
<b>Countersink Height:</b>	0.459 Inches Nominal
<b>Shear Strength:</b>	1038 Single Pounds Per Square Inch
<b>Countersink Angle:</b>	100.0 Degrees Nominal
<b>Material:</b>	Aluminum Alloy 2017 Washer
<b>Material Document And Classification:</b>	Qq-a-430 Fed Spec Single Material Response Washer
<b>Surface Treatment:</b>	Chromate Washer
<b>Surface Treatment Document And Classification:</b>	Mil-c-430, Class 1a Mil Spec Single Treatment Response Washer

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/BACR15GF6D7> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.