

Description

Fastener Length: 3/8", Thread: 2-56, Thread Length: 3/8

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	BACS12BG02AP6
Minimum Qty (MOQ):	1
NSN:	5305-01-090-7147
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N BACS12BG02AP6 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.309 Inches Minimum And 0.375 Inches Maximum
Fastener Length:	0.345 Inches Minimum And 0.375 Inches Maximum
Head Style:	Pan
Head Diameter:	0.155 Inches Minimum And 0.167 Inches Maximum
Head Height:	0.053 Inches Minimum And 0.062 Inches Maximum
Locking Feature:	Patch Threads
Internal Drive Style:	High-torque
Nominal Thread Diameter:	0.086 Inches
Thread Quantity Per Inch:	56
Minimum Tensile Strength:	150000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams5732 Assn Std Single Material Response Overall Or Ams5737 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjc

How to Order

Order this machine from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/BACS12BG02AP6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.