

P/N BACS12BP06P4

Description

Fastener Length: 1/4", Thread: 6-32, Thread Length: 3/16"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: BACS12BP06P4

Minimum Qty (MOQ): 10 EA

NSN: 5305-01-102-5506

Schedule B: 8108.90.3060

ECCN: EAR99

National Motor Freight: 096640, Screws, Iron Or Steel



^{*} See page 2 for technical characteristics

P/N BACS12BP06P4 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.101 Inches Minimum And 0.193 Inches Maximum
Fastener Length:	0.220 Inches Minimum And 0.250 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.249 Inches Minimum And 0.279 Inches Maximum
Locking Feature:	Patch Threads
Internal Drive Style:	High-torque
Nominal Thread Diameter:	0.138 Inches
Thread Quantity Per Inch:	32
Hardness Rating:	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Special Features:	Black Color
Material:	Steel Comp E4340 Overall Or Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8735 Overall Or Steel Comp 6150 Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjc

How to Order

Order this screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/BACS12BP06P4 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.