

Description

Fastener Length: 35/64", Thread: 10-32, Thread Length: 35/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | BACS12CK3U9 |
| Minimum Qty (MOQ): | 10 EA |
| NSN: | 5305-01-046-3241 |
| Schedule B: | 7318.15.6080 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N BACS12CK3U9 Specifications

| | |
|-------------------------------------|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.468 Inches Minimum And 0.560 Inches Maximum |
| Fastener Length: | 0.530 Inches Minimum And 0.560 Inches Maximum |
| Head Style: | Pan |
| Head Diameter: | 0.357 Inches Minimum And 0.373 Inches Maximum |
| Head Height: | 0.122 Inches Minimum And 0.133 Inches Maximum |
| Internal Drive Style: | Cross Recess Type 1 |
| Nominal Thread Diameter: | 0.190 Inches |
| Thread Quantity Per Inch: | 32 |
| Screw Material: | Steel |
| Screw Surface Treatment: | Passivate |
| Thread Series Designator: | Unf |
| Specification/standard Data: | 81205-bacs12ck Professional/Industrial Association Standard |

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/BACS12CK3U9> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.