

Description

Fastener Length: 35/64", Thread: 10-32, Thread Length: 35/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	BACS12CK3U9
Minimum Qty (MOQ):	10 EA
NSN:	5305-01-046-3241
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N BACS12CK3U9 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.468 Inches Minimum And 0.560 Inches Maximum
Fastener Length:	0.530 Inches Minimum And 0.560 Inches Maximum
Head Style:	Pan
Head Diameter:	0.357 Inches Minimum And 0.373 Inches Maximum
Head Height:	0.122 Inches Minimum And 0.133 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Screw Material:	Steel
Screw Surface Treatment:	Passivate
Thread Series Designator:	Unf
Specification/standard Data:	81205-bacs12ck Professional/Industrial Association Standard

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/BACS12CK3U9> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.