

**Description**

Fastener Length: 35/64", Thread: 10-32, Thread Length: 35/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	BACS12CK3U9
Minimum Qty (MOQ):	10 EA
NSN:	5305-01-046-3241
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N BACS12CK3U9 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.468 Inches Minimum And 0.560 Inches Maximum
<b>Fastener Length:</b>	0.530 Inches Minimum And 0.560 Inches Maximum
<b>Head Style:</b>	Pan
<b>Head Diameter:</b>	0.357 Inches Minimum And 0.373 Inches Maximum
<b>Head Height:</b>	0.122 Inches Minimum And 0.133 Inches Maximum
<b>Internal Drive Style:</b>	Cross Recess Type 1
<b>Nominal Thread Diameter:</b>	0.190 Inches
<b>Thread Quantity Per Inch:</b>	32
<b>Screw Material:</b>	Steel
<b>Screw Surface Treatment:</b>	Passivate
<b>Thread Series Designator:</b>	Unf
<b>Specification/standard Data:</b>	81205-bacs12ck Professional/Industrial Association Standard

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/BACS12CK3U9> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.