

Description

Fastener Length: 5/16", Thread: 10-32, Thread Length: 15/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|--------------------|------------------|
| SKU / Model: | BACS12ER3K5 |
| Minimum Qty (MOQ): | 15 EA |
| NSN: | 5305-01-589-7426 |

NO IMAGE
AVAILABLE

P/N BACS12ER3K5 Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.235 Inches Nominal |
| Fastener Length: | 0.325 Inches Nominal |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.375 Inches Nominal |
| Internal Drive Style: | Cross Recess Type Ii |
| Nominal Thread Diameter: | 0.190 Inches |
| Thread Quantity Per Inch: | 32 |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Screw Material: | Titanium Alloy Uns R56400 |
| Screw Material Document And Classification: | Ams 4928 Assn Std Single Material Response Or Ams 4967 Assn Std Single Material Response |
| Screw Surface Treatment: | Aluminum |
| Screw Surface Treatment Document And Classification: | Bms10-85, Type 1 Mfr Ref Single Treatment Response |
| Thread Series Designator: | Unjf |

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/BACS12ER3K5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.