

**Description**

Fastener Length: 0-31/32", Thread: 10-32, Thread Length: 53/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	BACS12GM316
Minimum Qty (MOQ):	25
NSN:	5305-01-051-4324
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N BACS12GM3-16 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.827 Inches Minimum And 0.920 Inches Maximum
<b>Fastener Length:</b>	0.969 Inches Minimum And 1.000 Inches Maximum
<b>Head Style:</b>	Flat Countersunk
<b>Head Diameter:</b>	0.332 Inches Minimum And 0.385 Inches Maximum
<b>Internal Drive Style:</b>	Cross Recess Type 1
<b>Nominal Thread Diameter:</b>	0.190 Inches
<b>Thread Quantity Per Inch:</b>	32
<b>Minimum Tensile Strength:</b>	125000 Pounds Per Square Inch
<b>Hardness Rating:</b>	26.0 Rockwell C Minimum And 32.0 Rockwell C Maximum
<b>Countersink Angle:</b>	100.0 Degrees Nominal
<b>Screw Material:</b>	Steel Comp 4037 Or Steel Comp 8630
<b>Screw Surface Treatment:</b>	Cadmium And Chromate
<b>Screw Surface Treatment Document And Classification:</b>	Qq-p-416,type 2,class 2 Fed Spec Single Treatment Response
<b>Special Features:</b>	Extended Point On Threaded End 57 To 63 Degrees
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/BACS12GM3-16> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.