

Description

Fastener Length: 1-1/8", Thread: 10-32, Thread Length: 0-63/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	BACS12GM318
Minimum Qty (MOQ):	20 EA
NSN:	5305-01-198-0732
National Motor Freight:	096630, Screws Noi Brass / Bronze / Copper



\* See page 2 for technical characteristics

## P/N BACS12GM3-18 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.9825 Inches Minimum And 1.0450 Inches Maximum
<b>Fastener Length:</b>	1.0625 Inches Minimum And 1.1250 Inches Maximum
<b>Head Style:</b>	Flat Countersunk
<b>Head Diameter:</b>	0.332 Inches Minimum And 0.385 Inches Maximum
<b>Internal Drive Style:</b>	Cross Recess Type 1
<b>Nominal Thread Diameter:</b>	0.1900 Inches
<b>Thread Quantity Per Inch:</b>	32
<b>Minimum Tensile Strength:</b>	125000 Pounds Per Square Inch
<b>Hardness Rating:</b>	26.0 Rockwell C Minimum And 32.0 Rockwell C Maximum
<b>Countersink Angle:</b>	99.0 Degrees Minimum And 101.0 Degrees Maximum
<b>Screw Material:</b>	Steel Comp 4037 Or Steel Comp 8630
<b>Screw Material Document And Classification:</b>	Mil-s-7839 Mil Spec All Material Responses
<b>Screw Surface Treatment:</b>	Cadmium
<b>Screw Surface Treatment Document And Classification:</b>	Qq-p-416 Ty2 Cl2 Fed Spec Single Treatment Response
<b>Special Features:</b>	Extended Point On Threaded End 57 To 63 Degrees
<b>Thread Series Designator:</b>	Unjf
<b>Specification/standard Data:</b>	81205-bacs12gm Manufacturers Standard

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/BACS12GM3-18> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.