

P/N BACS12GM3-18

Description

Fastener Length: 1-1/8", Thread: 10-32, Thread Length: 0-63/64

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: BACS12GM318

Minimum Qty (MOQ): 25

NSN: 5305-01-198-0732

ECCN: EAR99

National Motor Freight: 096630, Screws Noi Brass / Bronze / Copper



^{*} See page 2 for technical characteristics

P/N BACS12GM3-18 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.9825 Inches Minimum And 1.0450 Inches Maximum
Fastener Length:	1.0625 Inches Minimum And 1.1250 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.332 Inches Minimum And 0.385 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.1900 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Hardness Rating:	26.0 Rockwell C Minimum And 32.0 Rockwell C Maximum
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Steel Comp 4037 Or Steel Comp 8630
Screw Material Document And Classification:	Mil-s-7839 Mil Spec All Material Responses
Screw Surface Treatment:	Cadmium
Screw Surface Treatment Document And Classification:	Qq-p-416 Ty2 Cl2 Fed Spec Single Treatment Response
Special Features:	Extended Point On Threaded End 57 To 63 Degrees
Thread Series Designator:	Unjf
Specification/standard Data:	81205-bacs12gm Manufacturers Standard

How to Order

Order this machine screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/BACS12GM3-18 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.