

Description

Fastener Length: 1-1/8", Thread: 10-32, Thread Length: 0-63/64

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|--|
| SKU / Model: | BACS12GM318 |
| Minimum Qty (MOQ): | 25 |
| NSN: | 5305-01-198-0732 |
| ECCN: | EAR99 |
| National Motor Freight: | 096630, Screws Noi Brass / Bronze / Copper |

NO IMAGE
AVAILABLE

P/N BACS12GM3-18 Specifications

| | |
|---|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.9825 Inches Minimum And 1.0450 Inches Maximum |
| Fastener Length: | 1.0625 Inches Minimum And 1.1250 Inches Maximum |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.332 Inches Minimum And 0.385 Inches Maximum |
| Internal Drive Style: | Cross Recess Type 1 |
| Nominal Thread Diameter: | 0.1900 Inches |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 125000 Pounds Per Square Inch |
| Hardness Rating: | 26.0 Rockwell C Minimum And 32.0 Rockwell C Maximum |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Screw Material: | Steel Comp 4037 Or Steel Comp 8630 |
| Screw Material Document And Classification: | Mil-s-7839 Mil Spec All Material Responses |
| Screw Surface Treatment: | Cadmium |
| Screw Surface Treatment Document And Classification: | Qq-p-416 Ty2 Cl2 Fed Spec Single Treatment Response |
| Special Features: | Extended Point On Threaded End 57 To 63 Degrees |
| Thread Series Designator: | Unjf |
| Specification/standard Data: | 81205-bacs12gm Manufacturers Standard |

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/BACS12GM3-18> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.