

Description

BACS12GM3-20 Machine Screw

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	BACS12GM320
Minimum Qty (MOQ):	10
NSN:	5305-01-051-4325
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N BACS12GM3-20 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	1.046 Inches Minimum And 1.170 Inches Maximum
Fastener Length:	1.188 Inches Minimum And 1.250 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.332 Inches Minimum And 0.385 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Hardness Rating:	26.0 Rockwell C Minimum And 32.0 Rockwell C Maximum
Countersink Angle:	100.0 Degrees Nominal
Screw Material:	Steel Comp 4037 Or Steel Comp 8630
Screw Surface Treatment:	Cadmium And Chromate
Screw Surface Treatment Document And Classification:	Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response
Special Features:	Extended Point On Threaded End 57 To 63 Degrees
Thread Series Designator:	Unjf

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/BACS12GM3-20> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.